



- Material : High Quality Polyamide 6
- Degrees of Protection : IP 68 (EN 60529)
- The max, Instantaneous Temperature : -40°C to +105°C
- Short Term : up to +150° C
- Self-Extinguishing : UL94-HB / Free of Halogen Phosphorous and cadmium
- Color : Black & Gray
- Application : Connector for control box radio box or cables from electric machine, Water & Dust, Oil proof halogen free.

## » Product size



### PF Thread (JIS B0202)

Black	Gray	Thread	Øi (Min)	Øi (Max)	S	L1	L	ØD	SW1	SW2
FCG-G10B	FCG-G10G	G1/2"	3.5	6.5	20.9	15.0	43.9	24.4	22.6	18.0
FCG-G12B	FCG-G12G	G1/2"	4.0	8.0	20.9	15.0	46.2	28.8	25.5	21.3
FCG-G16B	FCG-G16G	G1/2"	7.0	12.3	20.9	15.0	47.2	28.6	25.4	25.4
FCG-G1622B	FCG-G1622G	G1/2"	12.0	15.2	20.9	15.0	53.4	38.2	34.0	34.0
FCG-G22B	FCG-G22G	G3/4"	12.0	18.0	26.4	15.0	53.4	38.2	34.0	34.0
FCG-G228B	FCG-G228G	G3/4"	18.0	20.3	26.4	15.0	53.4	49.0	43.4	43.4
FCG-G28B	FCG-G28G	G1"	18.0	26.0	33.2	15.0	53.4	49.0	43.4	43.4
FCG-G36B	FCG-G36G	G1 1/4"	22.0	33.0	41.9	19.0	67.7	59.0	53.0	51.6
FCG-G48B	FCG-G48G	G2"	36.0	42.0	59.6	19.0	69.7	74.0	66.5	67.0

(Dimensions in mm)