



SEMPERIT 

SUPERPAC SPC 3





Compact Hydraulic Hose construction with enhanced technical performance.



HOSE :

Tube	Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC)
Reinforcement	Three braids of high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber Note: various covers available
Temperature range	-40° C to 100° C / -40° F to +212° F (max 120° C/248° F intermittent)
Standard Branding	embossed

SEMPERIT  SPC 3 DN10 3/8" WP 500 BAR 7250 PSI . Q . . W . . z 

Impulse tested up to 400.000 Cycles!*

Nominal ∅		Inside ∅	Braid ∅	Outside ∅	Working pressure		Test pressure	Burst pressure	Bend radius	Weight
mm	inch	mm	mm	mm	bar	psi	bar	bar	mm	kg/m
10	3/8	9,9	16,8	20,9	500	7250	1000	2000	120	0,66
12	1/2	13,0	20,6	24,1	470	6820	940	1880	160	0,89
16	5/8	16,4	24,0	27,8	410	5950	820	1640	210	1,10
19	3/4	19,5	28,1	31,1	375	5440	750	1500	260	1,33
25	1	26,0	36,2	38,8	310	4500	620	1240	310	1,87

Publication date: July 2016 - Subject to changes without notice

*tested acc. to ISO6803:2008

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively subject to our general terms and conditions (available at www.semperitgroup.com).

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media indicated in the product catalogue. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to the continuous observance of all specifications and restrictions in our written product information, applicable laws and standards. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to EN853, 856, 857 and SAE J 517.

semperflex 
HYDRAULICS

A MEMBER OF THE SEMPERIT-GROUP