

List of standard model combinations

Motor base	Model	Rated power	Matching driver	Encoder cable	Power extension cable
40	RSM-M04J0130A	50W	RS100(E)	SES4-030	SMS-030
	RSM-M04J0330A	100W	RS100(E)	SES4-030	SMS-030
60	RSMA-M06J0630A	200W	RS200(E)	SES4-030	SMS-030
	RSMA-M06J1330A	400W	RS400(E)	SES4-030	SMS-030
80	RSMA-M08J2430A	750W	RS750(E)	SES4-030	SMS-030
	RSMA-M08J3230A	1KW	RS1000(E)	SES4-030	SMS-030
110	RSM-M11W4030A	1.2KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M11W5030A	1.5KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M11W6020A	1.2KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M11W6030A	1.8KW	RS2000(E)	SEH4-030	SMH-030
130	RSM-M13W5025A	1.3KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M13W6025A	1.5KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M13W7725A	2.0KW	RS2000(E)	SEH4-030	SMH-030
	RSM-M13W10025A	2.5KW	RS3000(E)	SEH4-030	SMH-030
	RSM-M13W15015A	2.3KW	RS3000(E)	SEH4-030	SMH-030
	RSM-M13W15025A	3.8KW	RS3000(E)	SEH4-030	SMH-030

* Driver with E is EtherCAT function

** Cable is 3 meters as standard, other specifications please specify when ordering

Servo cable list

Naming of AC servo cables

S **E** **S** **4** - **030**

① ② ③ ④ ⑤

- Cable series**
S: 220V AC servo
H: 380V high-voltage servo
D: Low-voltage brushless servo
- Cable category**
E: Encoder cable
M: Power extension cable
- Plug category**
S: Plastic Amp Head
H: Aviation plugs
- Number of cable cores**
Power cable 4 cores can be omitted
- Cable length**
Cable length is 3 meters

Motor cable of 80mm and below

Motor cable SMS-030
Color definition:

U	V	W	PE
Red	White	Black	Yellow&green

Encoder cable SES4-030



Motor cable of 110mm/130mm

Motor cable SMH-030
Color definition:

U	V	W	PE
Brown	Blue	Black	Yellow&green

Encoder cable SEH4-030

